



Safety Data Sheet

according to Regulation (EU) 2015/830

Issue date: 3/19/2020

Revision date:

Supersedes:

Version: 1.0

www.ardex.de

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Pandomo EP Neu Resin
 Product code : 37690

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Construction materials
 Industrial/Professional use spec : For professional use only
 Use of the substance/mixture : Substrate Preparation

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

ARDEX GmbH

Friedrich-Ebert-Strasse 45

D-58453 Witten-Annen - Germany

T 0049 (0)2302/664-0 - F 0049 (0)2302/664-355

sicherheitsdatenblatt@ardex.de - www.ardex.de

E-mail address of competent person responsible for the SDS : sicherheitsdatenblatt@ardex.de

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Germany	Vergiftungs-Informations-Zentrale	Mathildenstraße 1 79106 Freiburg	+49 (0) 761 19240	For medical information in German and English language

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302
 Acute toxicity (dermal), Category 4 H312
 Skin corrosion/irritation, Category 1A H314
 Serious eye damage/eye irritation, Category 1 H318
 Skin sensitisation, Category 1 H317
 Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Harmful in contact with skin. Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

GHS07

Signal word (CLP) : Danger

Hazardous ingredients : Isophorondiamine; m-phenylenebis(methylamine); Phenol, styrolized

Pandomo EP Neu Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

Hazard statements (CLP)	: H302+H312 - Harmful if swallowed or in contact with skin H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P261 - Avoid breathing dust, fume, gas, mist, spray, vapours. P280 - Wear protective gloves, eye protection. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
EUH-statements	: EUH205 - Contains epoxy constituents. May produce an allergic reaction.
Extra phrases	: Dispose of contents/container in accordance with regional/national/international/local regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isophorondiamine	(CAS-No.) 2855-13-2 (EC-No.) 220-666-8 (EC Index-No.) 612-067-00-9 (REACH-no) 01-2119514687-32	76 – 95	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Phenol, styrolized	(CAS-No.) 61788-44-1 (EC-No.) 262-975-0 (REACH-no) 01-2119980970-27	6 – 15	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
m-phenylenebis(methylamine)	(CAS-No.) 1477-55-0 (EC-No.) 216-032-5 (REACH-no) 01-2119480150-50	2.6 – 7.5	Skin Sens. 1B, H317 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
salicylic acid	(CAS-No.) 69-72-7 (EC-No.) 200-712-3 (EC Index-No.) 607-732-00-5 (REACH-no) 01-2119486984-17	0.2 – 2.5	Repr. 2, H361d Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Move to fresh air. If symptoms persist call a doctor.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Get medical advice/attention. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: None reasonably foreseeable.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Severe eye irritation.
Symptoms/effects after ingestion	: Irritating to the respiratory system and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Pandomo EP Neu Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Heat may cause pressure rise with explosion of tanks/drums.
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

Precautionary measures fire : Evacuate area.
Firefighting instructions : Contain the extinguishing fluids by bunding. Do not allow run-off from fire-fighting to enter drains or water courses.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Concerning personal protective equipment to use, see section 8.
Emergency procedures : Avoid contact with skin and eyes. Avoid breathing dust, fume, mist, gas, vapours, spray.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Do not attempt to take action without suitable protective equipment. Protective gloves. Safety glasses. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Do not allow to enter drains or water courses.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

See Heading 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : See Heading 8.
Precautions for safe handling : Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing spray, vapours, gas, mist, fume, dust, dust.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in original container. Keep container tightly closed in a cool, well-ventilated place.
Incompatible products : oxidizing materials. Strong bases. Strong acids.
Information on mixed storage : Keep away from food, drink and animal feeding stuffs.
Storage area : Keep out of frost.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Pandomo EP Neu Resin		
Germany	TRGS 900 Remark	keine Expositionsgrenzwerte bekannt

Pandomo EP Neu Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Respiratory protection not required in normal conditions. Safety glasses. Gloves.

Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,4		EN ISO 374

Eye protection:

Safety glasses

Type	Use	Characteristics	Standard
Safety goggles	Safety goggles recommended during refilling. Wear security glasses which protect from splashes	With side shields, Plastic	

Skin and body protection:

Wear suitable protective clothing

Type	Standard
Safety shoes, Skin protection appropriate to the conditions of use should be provided, Long sleeved protective clothing	

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Gas filters	A1	Vapour protection	



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Yellow.
Odour	: Amines.
Odour threshold	: No data available
pH	: 12.53
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: ≈ 100 °C
Flash point	: > 135 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.99 g/cm ³

Pandomo EP Neu Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 40 – 80 cP
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed or in contact with skin. Harmful in contact with skin or if inhaled.

ATE CLP (oral)	884.006 mg/kg bodyweight
ATE CLP (dermal)	1466.667 mg/kg bodyweight

Isophorondiamine (2855-13-2)	
LD50 oral rat	1030 mg/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (mg/l)	> 5.01 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

salicylic acid (69-72-7)	
LD50 oral rat	891 mg/kg bodyweight (Equivalent or similar to OECD 401, 14 day(s), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LD50 dermal rabbit	> 10000 mg/kg (Rabbit, Dermal)

Phenol, styrolized (61788-44-1)	
LD50 oral rat	2500 mg/kg
LD50 dermal rabbit	> 7940 mg/kg

m-phenylenebis(methylamine) (1477-55-0)	
LD50 oral rat	930 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 3100 mg/kg bodyweight (24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 inhalation rat (mg/l)	1.34 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol))

Skin corrosion/irritation	: Causes severe skin burns. pH: 12.53
Serious eye damage/irritation	: Causes serious eye damage. pH: 12.53
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

Pandomo EP Neu Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Isophorondiamine (2855-13-2)	
LC50 fish 1	110 mg/l (EU Method C.1, 96 h, Leuciscus idus, Semi-static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	23 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 72h algae (1)	37 mg/l (EU Method C.3, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)

salicylic acid (69-72-7)	
LC50 fish 1	1370 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Read-across, Lethal)
EC50 Daphnia 1	870 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 72h algae (1)	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, Desmodesmus subspicatus, Experimental value)

Phenol, styrolized (61788-44-1)	
EC50 Daphnia 1	> 0.249 mg/l (48 h, Daphnia sp., Literature study)
EC50 72h algae (1)	0.326 mg/l (Algae, Literature study)

m-phenylenebis(methylamine) (1477-55-0)	
LC50 fish 1	87.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oryzias latipes, Semi-static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	15.2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	33.3 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Experimental value, Nominal concentration)

12.2. Persistence and degradability

Isophorondiamine (2855-13-2)	
Persistence and degradability	Not readily biodegradable in water.

salicylic acid (69-72-7)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.95 g O ₂ /g substance
Chemical oxygen demand (COD)	1.58 g O ₂ /g substance
ThOD	1.623 g O ₂ /g substance
BOD (% of ThOD)	0.41 – 0.60

Phenol, styrolized (61788-44-1)	
Persistence and degradability	Biodegradability in soil: no data available. Not readily biodegradable in water.

m-phenylenebis(methylamine) (1477-55-0)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

Isophorondiamine (2855-13-2)	
BCF other aquatic organisms 1	3.16 (BCFWIN, QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.99 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

salicylic acid (69-72-7)	
Partition coefficient n-octanol/water (Log Pow)	2.25 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Phenol, styrolized (61788-44-1)	
Partition coefficient n-octanol/water (Log Pow)	6.24 – 7.77 (Experimental value, OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method)
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).

Pandomo EP Neu Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

m-phenylenebis(methylamine) (1477-55-0)	
BCF fish 1	< 2.7 (OECD 305: Bioconcentration: Flow-Through Fish Test, 42 day(s), Cyprinus carpio, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

Isophorondiamine (2855-13-2)	
Surface tension	3.47 N/m (23 °C)
Partition coefficient n-octanol/water (Log Koc)	2.97 (log Koc, QSAR)
Ecology - soil	Low potential for adsorption in soil.

salicylic acid (69-72-7)	
Partition coefficient n-octanol/water (Log Koc)	1.54 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Highly mobile in soil.

Phenol, styrolized (61788-44-1)	
Ecology - soil	No (test)data on mobility of the substance available.

m-phenylenebis(methylamine) (1477-55-0)	
Partition coefficient n-octanol/water (Log Koc)	3.11 (log Koc, QSAR)
Ecology - soil	Low potential for mobility in soil.

12.5. Results of PBT and vPvB assessment

Component	
Isophorondiamine (2855-13-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
salicylic acid (69-72-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
m-phenylenebis(methylamine) (1477-55-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available






SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code : 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
2735	2735	2735	2735	2735
14.2. UN proper shipping name				
AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorondiamine ; Phenol, styrolized)	AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorondiamine ; Phenol, styrolized)	Amines, liquid, corrosive, n.o.s. (Isophorondiamine ; Phenol, styrolized)	AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorondiamine ; Phenol, styrolized)	AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorondiamine ; Phenol, styrolized)
Transport document description				
UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorondiamine ; Phenol, styrolized), 8, III, (E), ENVIRONMENTALLY HAZARDOUS	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorondiamine ; Phenol, styrolized), 8, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 2735 Amines, liquid, corrosive, n.o.s. (Isophorondiamine ; Phenol, styrolized), 8, III, ENVIRONMENTALLY HAZARDOUS	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorondiamine ; Phenol, styrolized), 8, III, ENVIRONMENTALLY HAZARDOUS	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (Isophorondiamine ; Phenol, styrolized), 8, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
8	8	8	8	8
				

Pandomo EP Neu Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : C7
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Transport category (ADR) : 3
Orange plates :



Tunnel restriction code (ADR) : E

- Transport by sea

Special provisions (IMDG) : 223, 274
Limited quantities (IMDG) : 5 L
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B
Segregation (IMDG) : SG35

- Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y841
PCA limited quantity max net quantity (IATA) : 1L
PCA max net quantity (IATA) : 5L

- Inland waterway transport

Classification code (ADN) : C7
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1

- Rail transport

Classification code (RID) : C7
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Transport category (RID) : 3

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

Other information, restriction and prohibition regulations : Gemäß ArbmedVV Organisation der Vorsorge "Umgang mit unausgehärteten Epoxidharzen".

15.1.2. National regulations

Germany

Regulatory reference : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)
Storage class (LGK) : LGK 8A - Combustible corrosive substances

Pandomo EP Neu Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)
 GHS CODE : RE30 - Epoxy resin products, sensitising, total solid

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Acute Tox. 4 (Oral)	H302
Acute Tox. 4 (Dermal)	H312
Skin Corr. 1A	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 3	H412

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.

Pandomo EP Neu Resin

Safety Data Sheet

according to Regulation (EU) 2015/830

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.