



Safety Data Sheet

according to Regulation (EU) 2015/830

Issue date: 10/5/2016

Revision date: 6/18/2021

Supersedes version of:
10/5/2016

Version: 2.0

www.ardex.de

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Pandomo K 2
Product code : 53125

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : Construction materials
Use of the substance/mixture : PANDOMO
Floor Levelling Compounds
Function or use category : Construction materials

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

ARDEX GmbH
Friedrich-Ebert-Strasse 45
D-58453 Witten-Annen - Germany
T 0049 (0)2302/664-0 - F 0049 (0)2302/664-355
sicherheitsdatenblatt@ardex.de - www.ardex.de
E-mail address of competent person responsible for the SDS : sicherheitsdatenblatt@ardex.de

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Germany	Vergiftungs-Informationen-Zentrale	Breisacher Strasse 86b 79110 Freiburg	+49 (0) 761 19240	For medical information in German and English language

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

Causes skin irritation. Causes serious eye damage.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children.
EUH-statements : EUH208 - Contains Portland cement. May produce an allergic reaction.
EUH210 - Safety data sheet available on request.
Extra phrases : Dispose of contents/container in accordance with regional/national/international/local regulations.

Labelling according to Directive 67/548/EEC or 1999/45/EC

2.3. Other hazards

Other hazards which do not result in classification : The product contains chromate reducer, whereby the content of water-soluble chromium (VI) is less than 0.0002%.
With proper storage (dry) and consumption within the specified storage time, a sensitizing

Pandomo K 2

Safety Data Sheet

according to Regulation (EU) 2015/830

effect of the cement / binder by contact with skin cannot occur (H317 or EUH203 can therefore be omitted).

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Portland cement	(CAS-No.) 65997-15-2 (EC-No.) 266-043-4	< 1	Skin Sens. 1, H317 Eye Dam. 1, H318 Skin Irrit. 2, H315 STOT SE 3, H335

Comments : Chromium (VI) compounds < 2 ppm

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : If the person is fully conscious, make him/her drink plenty of water. Never give an unconscious person anything to drink. Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : high volume water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : No fire hazard.

Explosion hazard : None.

Hazardous decomposition products in case of fire : None.

5.3. Advice for firefighters

Precautionary measures fire : No specific measures are necessary.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Precautions for safe handling. See Heading 7.

Emergency procedures : Avoid contact with skin and eyes.

6.1.2. For emergency responders

Emergency procedures : No specific measures are necessary.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

Pandomo K 2

Safety Data Sheet

according to Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
 Methods for cleaning up : Mechanically recover the product. Minimise generation of dust. Collect spillage. Do not use compressed air for cleaning.

6.4. Reference to other sections

For further information refer to section 13. See Heading 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : See Heading 8.
 Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment.
 Hygiene measures : Wear protective gloves. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from moisture. Store in a dry place. The product contains chromate reducer, whereby the content of water-soluble chromium (VI) is less than 0.0002%.
 With proper storage (dry) and consumption within the specified storage time, a sensitizing effect of the cement / binder by contact with skin cannot occur (H317 or EUH203 can therefore be omitted).
 Incompatible materials : Aluminium. ammonium salts. Acids.
 Storage area : dry.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Pandomo K 2		
Germany	Local name	Allgemeiner Staubgrenzwert - Alveolengängige/Einatembare Fraktion
Germany	AGW (OEL TWA) [1]	1.25 mg/m ³ (A) 10 mg/m ³ (E)
Germany	Remark	AGS;DFG

Exposure limit values for the other components

calcium sulfate (7778-18-9)			
Germany	Local name	Calciumsulfat	
Germany	AGW (OEL TWA) [1]	6 mg/m ³ (A)	
Germany	Remark	DFG	

quartz, conc respirable crystalline silica<1 % (14808-60-7)			
EU	Local name	Silica crystalline (Quartz)	
EU	IOEL TWA	0.1 mg/m ³ (Respirable fraction)	
EU	Remark	(Year of adoption 2003)	

calcium hydroxide (1305-62-0)			
EU	Local name	Calcium dihydroxide	
EU	IOEL TWA	1 mg/m ³ (Respirable fraction)	
EU	IOEL STEL	4 mg/m ³ (Respirable fraction)	
Germany	Local name	Calciumdihydroxid	
Germany	AGW (OEL TWA) [1]	1 mg/m ³ (E)	
Germany	Remark	Y;EU;DFG	

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Safety glasses. Dust formation: dust mask. Gloves.

Pandomo K 2

Safety Data Sheet

according to Regulation (EU) 2015/830

Hand protection:

Protective gloves. The following materials are suitable for protective gloves:
Nitrile impregnated cotton gloves (layer thickness of about 0,15 mm).

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

If the occupational exposure limit is exceeded:



Environmental exposure controls:

Avoid release to the environment.

Other information:

Use care during processing to minimize generation of dust. Avoid creating or spreading dust.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Colour	: white.
Odour	: odourless.
Odour threshold	: No data available
pH	: 11
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: > 1250 °C
Freezing point	: Not applicable
Boiling point	: Not applicable
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: Not applicable
Density	: 2.75 – 3.2 g/cm ³
Solubility	: Water: 0.1 – 1.5 g/l @ 20°C
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: Not applicable
Explosive properties	: None.
Oxidising properties	: None.
Explosive limits	: Not applicable

9.2. Other information

Bulk density	: 900 – 1300 kg/m ³
--------------	--------------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with water.

10.2. Chemical stability

Stable under normal conditions.

Pandomo K 2

Safety Data Sheet

according to Regulation (EU) 2015/830

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Acids. ammonium salts. Aluminium.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified pH: 11
Serious eye damage/irritation	: Not classified pH: 11
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

Pandomo K 2

Viscosity, kinematic	Not applicable
----------------------	----------------

Potential adverse human health effects and symptoms : Irritation: severely irritant to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Portland cement (65997-15-2)

LC50 - Fish [1]	> 1000 mg/l (96 h, Pisces)
-----------------	----------------------------

12.2. Persistence and degradability

Pandomo K 2

Persistence and degradability	Not applicable. Inorganic Particulate Substances.
BOD (% of ThOD)	Not applicable

Portland cement (65997-15-2)

Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

Pandomo K 2

Bioaccumulative potential	No bioaccumulation.
---------------------------	---------------------

Portland cement (65997-15-2)

Bioaccumulative potential	Bioaccumulation: not applicable.
---------------------------	----------------------------------

12.4. Mobility in soil

Pandomo K 2

Ecology - soil	None.
----------------	-------

Portland cement (65997-15-2)

Ecology - soil	No (test)data on mobility of the substance available.
----------------	---

Pandomo K 2

Safety Data Sheet

according to Regulation (EU) 2015/830

12.5. Results of PBT and vPvB assessment

Pandomo K 2	
PBT: not relevant – no registration required	
vPvB: not relevant – no registration required	
Component	
Portland cement (65997-15-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Avoid release to the environment.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 17 01 01 - concrete 10 13 14 - waste concrete and concrete sludge For residues 01 04 07* - wastes containing dangerous substances from physical and chemical processing of non-metalliferous minerals

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number		
Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name		
Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)		
Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Not applicable	Not applicable	Not applicable
No supplementary information available		

14.6. Special precautions for user

- Overland transport

Not applicable

- Transport by sea

Not applicable

- Air transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Pandomo K 2

Safety Data Sheet

according to Regulation (EU) 2015/830

- Other information, restriction and prohibition regulations : 1. Cement and cement-containing mixtures shall not be placed on the market, or used, if they contain, when hydrated, more than 2 mg/kg (0,0002 %) soluble chromium VI of the total dry weight of the cement.
2. If reducing agents are used, then without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of cement or cement-containing mixtures is visibly, legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI below the limit indicated in paragraph 1.
3. By way of derogation, paragraphs 1 and 2 shall not apply to the placing on the market for, and use in, controlled closed and totally automated processes in which cement and cement-containing mixtures are handled solely by machines and in which there is no possibility of contact with the skin.
4. The standard adopted by the European Committee for Standardization (CEN) for testing the water-soluble chromium (VI) content of cement and cement-containing mixtures shall be used as the test method for demonstrating conformity with paragraph 1.
5. Leather articles coming into contact with the skin shall not be placed on the market where they contain chromium VI in concentrations equal to or greater than 3 mg/kg (0,0003 % by weight) of the total dry weight of the leather.
6. Articles containing leather parts coming into contact with the skin shall not be placed on the market where any of those leather parts contains chromium VI in concentrations equal to or greater than 3 mg/kg (0,0003 % by weight) of the total dry weight of that leather part.
7. Paragraphs 5 and 6 shall not apply to the placing on the market of second-hand articles which were in end-use in the Union before 1 May 2015.

15.1.2. National regulations

Germany

- Regulatory reference : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)
- Storage class (LGK, TRGS 510) : LGK 13 - Non-combustible solids
- Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)
- GISCODE : ZP1 - Products containing cement, low in chromate
- EMICODE : EC 1 PLUS - very low emission
- TA Luft : 5.2.1 Total Dust, including Micro Dust
- National Rules and Recommendations : TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure
TRGS 510: Storage of hazardous substances in non-stationary containers
TRGS 900: Occupational Exposure Limits

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:

EUH208	Contains Portland cement. May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.